



## APWH

### All Purpose PVC Water Hose

#### Description

The all purpose water hose range offers outstanding low temperature characteristics combined with flexibility and has been designed for the professional.

#### Applications:

Suitable for general purpose water applications, including sports grounds, agricultural, horticultural and domestic garden applications.

#### Construction

Two layers of smooth PVC bonded together

#### Special Features

- Professional quality PVC water hose with braided textile reinforcement for added strength
- Suitable for general purpose water applications, including sports grounds, agricultural and horticultural applications
- Made from abrasion resistant PVC compounds
- High flexibility
- Silicone free
- Abrasion resistance – good
- Made from Cadmium free materials
- Kink resistance – good
- Outstanding all year round flexibility
- Polyester fibre reinforcement

#### Colour

Yellow and Translucent Green

#### Size Range

12mm to 25mm ID  
(1/2" to 1")

#### Standard Length

30 metres supplied in a coil

#### Temperature Range

-10°C to +55°C

# APWH - All Purpose PVC Water Hose



od outside diameter  
id internal diameter

note: all dimensions in mm

## APWH - All Purpose PVC Water Hose, Yellow and Translucent Green

Product Ref.	Internal Dia. mm	Nominal Internal Dia. Inches	External Dia. mm	Working Pressure Bar	Min Bending Radius mm	Weight Kg/Coil	Coil Length Metres
APWH12.5	12.5	1/2	17.0	10.0	62.5	4.56	30
APWH19	19.0	3/4	24.5	10.0	95.0	8.25	30
APWH25	25.0	1	31.0	10.0	125.0	11.91	30

All sizes are nominal and normal manufacturing tolerances apply.

For further information please call Griflex on 01675 464803.

- (i) Maximum working pressure is based on a factor of safety of 3:1 on burst pressure at 23°C (+/- 2°C). Working pressure reduces with increasing temperatures.
- (ii) Lengths detailed above are as standard, however variations may be available subject to minimum order quantities. Weights are approximate dependant upon working tolerance and density of materials.
- (iii) Bending diameter information is intended as a guide to the minimum bend radius at 23°C ambient temperature without restricting the bore. It does not mean that the hose cannot be bent below the given dimensions but restriction is likely to occur.
- (iv) Errors, omissions and amendments excepted. As part of continuing product development GRIFLEX reserve the right to alter product specifications without prior notice. Data given is correct at time of compilation. Product specification and application data is for guidance only and does not constitute a warranty of any kind, either expressed or implied for GRIFLEX products or their suitability for a specific purpose.

**GRIFLEX**  
hose & ducting solutions

[A] Roman Way, Coleshill, Birmingham B46 1HG

[T] +44 (0)1675 464803 [F] +44 (0)1675 465924

[E] sales@griflex.com [W] www.griflex.com