



DDH Diesel Drop Hose

Description

Manufactured from a compound containing nitrile, offering excellent flexibility & kink resistance, this hose is designed for the transportation of fuel oils. Minimum frictional loss is achieved by the smooth bore.

Applications

Delivery of Diesel, Petrol and mineral based oils.

Construction

Two layers of nitrile PVC bonded together encapsulating high tensile polyester fibres.

Special Features

- Excellent abrasion resistance
- Outstanding resistance to ageing
- Highly Flexible
- Kink resistant
- Good resistance to a wide range of chemicals

Colour

Standard - Black

Size Range

19mm & 25mm ID
($\frac{3}{4}$ " & 1")

Standard Length

50 metres / supplied in a coil
Subject to minimum order quantity, longer lengths are available to order

Temperature Range

-10°C to +55°C

DDH - Diesel Drop Hose



od outside diameter
id internal diameter

note: all dimensions in mm

DDH - Diesel Drop Hose, Black

Product Ref.	Internal Dia. mm	Nominal Internal Dia. Inches	External Dia. mm	Working Pressure Bar	Min Bending Radius mm	Weight Kg/Coil	Coil Length Metres
DDH19/28	19.0	3/4	28.0	7.0	140.0	25.50	50
DDH25/34	25.0	1	34.0	7.0	180.0	32.00	50

All sizes are nominal and normal manufacturing tolerances apply.

For further information please call Griflex on 01675 464803.

- (i) Maximum working pressure is based on a factor of safety of 3:1 on burst pressure at 23°C (+/- 2°C). Working pressure reduces with increasing temperatures.
- (ii) Lengths detailed above are as standard, however variations may be available subject to minimum order quantities. Weights are approximate dependant upon working tolerance and density of materials.
- (iii) Bending diameter information is intended as a guide to the minimum bend radius at 23°C ambient temperature without restricting the bore. It does not mean that the hose cannot be bent below the given dimensions but restriction is likely to occur.
- (iv) Errors, omissions and amendments excepted. As part of continuing product development GRIFLEX reserve the right to alter product specifications without prior notice. Data given is correct at time of compilation. Product specification and application data is for guidance only and does not constitute a warranty of any kind, either expressed or implied for GRIFLEX products or their suitability for a specific purpose.

GRIFLEX
hose & ducting solutions

[A] Roman Way, Coleshill, Birmingham B46 1HG

[T] +44 (0)1675 464803 [F] +44 (0)1675 465924

[E] sales@griflex.com [W] www.griflex.com