

Fittings - Hose Fittings

NYLON 6-6




Working pressure
Up to 14 BAR
(200 psi) at 20 °C



Temperature
-20 °C - 110 °C
(subject to application)



Fittings' dimensions
refer to tube ID or OD, with respect to
the common application.




Reducing T Hose Connector

Cat. No.	ID mm	ID1 mm	L mm	L1 mm	Colour
12447245448	5	4	50.7	25.7	Blue
12447246458	6	5	55.7	31.8	
12447248468	8	6	61.5	36.2	
12447250488	10	8	66.5	39.3	
12447252508	12	10	70.6	44.5	
12447254528	14	12	76.7	44.5	
12447256548	16	14	79.5	51.1	
12447259568	19	16	84.6	55.4	

Note: Packing 25 unit


Cat. No.	ID inch	ID1 inch	L mm	L1 mm	Colour
12257203023	3/16"	5/32"	50.6	25.9	Grey
12257204033	1/4"	3/16"	55.8	32.0	
12257205043	5/16"	1/4"	61.5	36.2	
12257206053	3/8"	5/16"	66.5	39.3	
12257208063	1/2"	3/8"	70.3	43.5	
12257209083	5/8"	1/2"	76.3	48.0	
12257210093	3/4"	5/8"	79.4	51.0	
12257212103	7/8"	3/4"	84.3	55.2	

Note: Packing 25 unit



Female Swivel Straight Hose Connector - Conical Seat

Cat. No.	ID mm	F (BSPT)	L mm	SW	Colour
22444644028	4	1/8"	27.5	13	Blue
22444644048	4	1/4"	31.7	17	
22444645028	5	1/8"	32.0	13	
22444645048	5	1/4"	36.2	17	
22444645068	5	3/8"	36.0	20	
22444646048	6	1/4"	37.3	17	
22444646068	6	3/8"	36.8	20	
22444646088	6	1/2"	39.5	24	
22444648048	8	1/4"	41.3	17	
22444648068	8	3/8"	40.8	20	
22444648088	8	1/2"	43.6	24	
22444648128	8	3/4"	43.4	30	
22444650068	10	3/8"	42.8	20	
22444650088	10	1/2"	43.6	24	
22444650128	10	3/4"	45.6	30	
22444652088	12	1/2"	46.7	24	
22444652128	12	3/4"	46.5	30	
22444654088	14	1/2"	48.9	24	
22444654128	14	3/4"	48.1	30	
22444656128	16	3/4"	48.5	30	Black
22444659128	19	3/4"	49.3	30	
22444648042	8	1/4"	41.3	17	
22444650062	10	3/8"	42.8	20	
22444652082	12	1/2"	46.7	24	



Female Swivel Straight Hose Connector

Cat. No.	ID mm	F (BSPT)	L mm	SW	Colour
22454765168	24	1"	61.8	44	Blue