

FLOW PRODUCTS

Fittings - Threaded Connectors


NYLON 6-6



Working pressure
Up to 14 BAR
(200 psi) at 20 °C



Temperature
-20 °C - 110 °C
(subject to application)



BSPT Pipe T

Cat. No.	M (BSPT)	L mm	L1 mm	Colour
12016402008	1/8"	39.8	24.1	Blue
12016404008	1/4"	44.0	26.2	
12016406008	3/8"	50.5	32.0	
12016408008	1/2"	64.0	40.3	

Note: Packing 25 unit

NPT Pipe T

Cat. No.	M (NPT)	L mm	L1 mm	Colour
12026402003	1/8"	39.3	24.0	Grey
12026404003	1/4"	48.4	28.5	

Note: Packing 25 unit

BSPT Pipe Reducing Branch T

Cat. No.	M (BSPT)	M1 (BSPT)	L mm	L1 mm	Colour
12017102048	1/8"	1/4"	39.7	26.4	Blue
12017104028	1/4"	3/8"	43.3	24.2	
12017104068	1/4"	3/8"	43.3	38.2	
12017106048	3/8"	1/4"	60.2	26.4	
12017108068	1/2"	3/8"	64.2	38.2	
12017106088	3/8"	1/2"	60.2	40.4	

Note: Packing 25 unit

NPT Pipe Reducing Branch T

Cat. No.	M (BSPT)	M1 (BSPT)	L mm	L1 mm	Colour
12027104023	1/4"	1/8"	48.4	24.0	Grey

Note: Packing 25 unit

BSPT Pipe Reducing Run T

Cat. No.	M (BSPT)	M1 (BSPT)	L mm	L1 mm	Colour
12017204028	1/4"	1/8"	41.8	26.3	Blue
12017206048	3/8"	1/4"	48.3	30.8	
12017208068	1/2"	3/8"	62.0	40.0	
12017202048	1/8"	1/4"	42.7	25.5	
12017204068	1/4"	3/8"	48.5	31.0	
12017206088	3/8"	1/2"	62.0	38.2	

Note: Packing 25 unit

NPT Pipe Reducing Run T

Cat. No.	M (NPT)	M1 (NPT)	L mm	L1 mm	Colour
12027204023	1/4"	1/8"	41.8	26.3	Grey

Note: Packing 25 unit



Fittings - Quick Release



Working pressure
Up to 14 BAR
(200 psi) at 20 °C



Temperature
4 °C - 90 °C
(subject to application)

The special quick connector offers a fast and reliable push-to-connect mechanism.

The movable outer sleeve locks the plug into the socket.

When the plug is disconnected, the socket acts as a shut-off valve.

A variety of plugs can be connected and used, according to hydraulic or pneumatic needs.

part	material
Body	Nylon 6-6
Internal parts	Acetal
spring	SS 316

Quick Release Socket


Cat. No.	F (BSPT)	L mm	SW	O-ring	Colour
22080004000	1/4"	44.0	19	NBR	Red
22081104002	1/4"	44.0	19	EPDM	



Plug - External Thread

Cat. No.	M (BSPT)	SW	Colour
12081404006	1/4"	312	Red


Note: Packing 25 unit



Plug - Internal Thread

Cat. No.	F (BSPT)	L mm	SW	Colour
12081504006	1/4"	28.6	17	Red

Note: Packing 25 unit



Plug - Hose Connector

Cat. No.	ID mm	L mm	D	Colour
12081645006	5	37.8	16.7	Red
12081646006	6	39.8	16.7	
12081648006	8	43.2	16.8	
12081650006	10	43.2	16.8	
12081652006	12	43.2	16.8	

Note: Packing 25 unit

