Data

Working temperature:	-20 °C to +70 °C
Working pressure:	max 10 bar
Flow (acc. to ISO 6358)	
C:	0,9 Nl/s, bar
Qn (P1=6 bar, Δp=1 bar):	3,6 l/s
Qmax:	6,3 l/s
Cv:	0,21

	Symbol	Actuator	Return	Mounting	Changeover **force** at 6 bar	Weight kg	Order code
		Push-button Red	Spring	Panel mounted	34,5 N	0,46	**VA15-HIS4**
		Hand lever Held in two positions	Hand lever	Panel mounted	9 N	0,63	**VA15-HB24**
				Side mounted	9 N	0,45	**VA15-HB2**
		Hand lever Held in three positions	Hand lever	Panel mounted Closed centre position	9 N	0,63	**VA15-HB34**
		Hand lever Held in three positions	Hand lever	Panel mounted Exhausted centre position	9 N	0,63	**VA15-XHB34**
		Hand lever Three positions self-centring	Hand lever	Panel mounted Closed centre position	9 N	0,63	**VA15-HC4**
		Hand lever Three positions self-centring	Hand lever	Panel mounted Exhausted centre position	9 N	0,63	**VA15-XHC4**
		Knob Red Two positions	Knob	Panel mounted	5 N	0,58	**VA15-KL24**
				Side mounted	5 N	0,42	**VA15-KL2**
		Knob Red	Spring	Panel mounted	34,5 N	0,60	**VA15-KS4**
		Knob Red Two positions	Knob/Air signal	Panel mounted	8 N*	0,61	**VA15-KL2A4**

*Without signal pressure. Signal pressure min 3 bar at 6 bar supply pressure.