




Mini industrial coupling with plug profile according to ISO 6150 C. Popular profile in analytical and medical technology. Above average flow rate performance for liquid and gaseous media.

- Available on request:
 - with additional end connections
 - other seals for different temperature ranges and fluids



ISO C Profile



Working Pressure*:
up to 35 bar

Material:

- Coupling: AISI 316 L
- Plug: AISI 316 L
- Seals: FKM

Working Temperature:
-15°C up to +200°C (FKM)

Flow Rate Air:
160 l/min.
inlet pressure 6 bar, pressure drop 0.5 bar

Flow Rate Air:
2.2 l/min.
pressure drop 0.5 bar

* maximum static working pressure with design factor 4 to 1.




Double Shut-off



Double Shut-off

303KBAW Coupler with valve, Male Thread


Stainless Steel AISI 316 L, FKM



| A | HEX | L | L1 | D |
|-----------------------------------|-----|----|----|----|
| G1/8 303KBAW10EVX | 14 | 43 | 7 | 18 |
| G1/4 303KBAW13EVX | 17 | 45 | 9 | 18 |

303KBKO Coupler with valve, with Plastic Hose Connection


Stainless Steel AISI 316 L, FKM



| A | HEX | G | L | L1 | L2 | D |
|------------------------------------|-----|-------|----|----|----|----|
| 4 x 6 303KBK006EVX | 14 | M10x1 | 49 | 7 | 6 | 18 |
| 6 x 8 303KBK008EVX | 14 | M12x1 | 49 | 7 | 6 | 18 |

303KBIW Coupler with valve, Female Thread


Stainless Steel AISI 316 L, FKM




| A | HEX | L | L1 | D |
|-----------------------------------|-----|----|----|----|
| G1/8 303KBIW10EVX | 14 | 43 | 9 | 18 |
| G1/4 303KBIW13EVX | 17 | 45 | 9 | 18 |

303SBAW Plug with valve, Male Thread

Stainless Steel AISI 316 L, FKM




| A | HEX | L | L1 |
|-----------------------------------|-----|------|----|
| G1/8 303SBAW10EVX | 14 | 48.5 | 7 |
| G1/4 303SBAW13EVX | 17 | 50.5 | 9 |



Double Shut-off

303SBIW Plug with valve, Female Thread

Stainless Steel AISI 316 L, FKM




A

HEX L L1

| | | | | |
|------|---------------------|----|------|---|
| G1/8 | 303SBIW10EVX | 14 | 48.5 | 9 |
| G1/4 | 303SBIW13EVX | 17 | 50.5 | 9 |

303SBKO Plug with valve, with Plastic Hose Connection

Stainless Steel AISI 316 L, FKM



A

HEX G L L1 L2

| | | | | | | |
|-------|---------------------|----|-------|------|---|---|
| 4 x 6 | 303SBKO06EVX | 14 | M10x1 | 54.5 | 7 | 6 |
| 6 x 8 | 303SBKO08EVX | 14 | M12x1 | 54.5 | 7 | 6 |