



The mini series offer space saving solutions for frequent disconnection of tubing or pneumatic tools.

- Compact and ergonomic
- Easy identification of circuits
- Easy disconnection / single hand operation

own Profile

KA Single Shut-Off

Working Pressure*:
up to 20 bar

Material:

- **Coupling:** Technical polymer, nickel plated brass
- **Plug:** nickel plated brass
- **Seals:** NBR

Working Temperature:
-20°C up to +60°C (NBR)


Flow Rate Air:

165 NI/min.
inlet pressure 6 bar, pressure drop 0.6 bar

Single Shut-Off

0171 Coupler with valve, Male BSPT and Parallel Metric Thread

Technical polymer, Nickel-plated brass, NBR



DN	C		E	F	L	Kg
2	M7x1	0171 02 55 01	6	10	21	
2	R1/8	0171 02 10 01	7.5	10	21	
2	R1/8	0171 02 10 02	7.5	10	21	
2	R1/8	0171 02 10 03	7.5	10	21	
2	R1/8	0171 02 10 04	7.5	10	21	
2	R1/8	0171 02 10 05	7.5	10	21	

Single shut-off
Mini Series (DN 2): single shut-off= 165 NI/min

Single Shut-Off

0184 Plug without valve, Male BSPT Thread

Nickel-plated brass




DN	C		F	L	Kg
2	R1/8	0184 02 10	10	13	

Probe without Shut-off


0181 Plug without valve, Male BSPT Thread

Nickel-plated brass



DN	ØD	ØD1		L	L1	Kg
2	3	3.3	0181 03 04	11.5	13.5	

Probe without Shut-off



Double Shut-off

0183 Plug with valve, Male BSPT Thread

Nickel-plated brass, NBR



DN C 

F L Kg

2 R1/8 **0183 02 10**

10 13

Probe with Shut-off