



The Standard range offers a robust solution and a good compromise between space and flow performance.

- Robust and adapted to demanding application
- Good corrosion resistance thanks to nickel plating

own Profile

KA
Single Shut-Off

**Working Pressure\*:**  
up to 20 bar

**Material:**

- Coupling: Nickel plated brass
- Plug: Zinc plated blister steel
- Seals: NBR

**Working Temperature:**  
-20°C up to +80°C (NBR)


**Flow Rate Air:**  
480 NI/min.  
inlet pressure 6 bar, pressure drop 0.6 bar



Single Shut-Off


## 0172 Coupler with valve, Female BSPP Thread

Nickel-plated brass, NBR



DN	C		E	F	G	L	Kg
5	G1/4	<b>0172 05 13</b>	11	19	21	47	


Standard Series: single shut-off = 480 NI/min



Single Shut-Off

## 0186 Plug without valve, Female BSPP Thread

Zinc-plated blister steel



DN	C		E	F	L	Kg
5	G1/4	<b>0186 05 13</b>	12	17	17	

Probe without Shut-off

## 0187 Plug without valve, Male BSPP Thread

Zinc-plated blister steel




DN	C		E	F	L	Kg
5	G1/8	<b>0187 05 10</b>	7	14	4	
5	G1/4	<b>0187 05 13</b>	9.5	17	5	

Probe without Shut-off

## 0185 Plug without valve, with Barb Connection for Flexible Tubing

Zinc-plated blister steel



DN	ØD	ØD1		L	Kg
5	4	6	<b>0185 04 00</b>	22.5	
5	7	9	<b>0185 07 00</b>	22.5	
5	10	12.2	<b>0185 10 00</b>	22.5	

Probe without Shut-off



Single Shut-Off

## 0189 Double Plug

Zinc-plated blister steel



DN 

F L Kg

5 **0189 05 00**

12 4

Probe without Shut-off