

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Morris Hydraulic &  
Compressor Oils  
Page 1 of 5  
Number 200  
Revision: 4  
01.09.03

## Safety data sheet

### 1. PRODUCT INFORMATION

Product Name Morris Liquimatic (1-8), Tempo (32 to150), ArcatoR32, R46, R68 AR46,3CL.  
Application **Hydraulic and Compressor Oils**  
Company **Morris Lubricants**  
Address **Castle Foregate, Shrewsbury, SY1 2EL, United Kingdom**  
Telephone No (+44) (0)1743 232200  
Fax No (+44) (0)1743 353584

### 2. COMPOSITION

Component Name	CAS No.	% Mass	Symbols/O E L	R Phrases
Mineral Oil Hydrotreated (IP346 DMSO Extract L 3%)	Mixture	>90	O E L	
Sterically hindered phenol	-	0.1-0.5	N	R51/53
Dithiophosphoric acid Ester	-	0.1- 0.5	N	R51/53

### 3. HAZARDS

This product is NOT classified as hazardous under current UK Health/Safety/Environmental Legislation, but should be handled in accordance with good industrial hygiene and safety practices.

Adverse Health Effects Repeated contact with the skin may result in skin irritation.

Other Hazards Large spills may cause contamination of soil and water.

### 4. FIRST AID MEASURES

Inhalation If inhalation of mist fumes or vapour causes irritation to the nose or throat or coughing remove to fresh air. If symptoms persist obtain medical advice.

Skin contact Wash skin thoroughly using soap and water.

Eye contact Rinse with plenty of water (also under eyelids) for at least 10 minutes and seek medical attention if symptoms persist.

Ingestion Seek medical attention. **DO NOT INDUCE VOMITING.**



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Morris & Company, Welsh Bridge, Shrewsbury

Registered in England No. 185693



Certificate No. EMS 60044  
BS EN ISO14001 1996

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Morris Hydraulic &  
Compressor Oils  
Page 2 of 5  
Number 200  
Revision: 4  
01.09.03

## Safety data sheet

### 5. FIRE-FIGHTING MEASURES

Extinguishing Media	Use carbon dioxide, foam or water spray. Prevent water used in spray from entering watercourses.
Not to be used	Direct water jet. (Use water only to keep fire exposed containers cool.)
Special fire fighting procedures	In the event of a large fire self-contained breathing apparatus should be worn.
WARNING	Heat from a fire could possible result in drums bursting.

### 6. ACCIDENTAL RELEASE MEASURES

Contain and collect spillage with help of absorbent materials such as floor granules. Protect drains from potential spills to minimise contamination. If spillage enters drains call Environment Agency Emergency hotline on 0800 807060. Product Waste should be disposed of according to Item 13.

### 7. HANDLING & STORAGE

Handling	Precautions should be taken against skin and eye contact. Avoid inhalation of vapour mist or fume. Do not wear contaminated clothing. Wear safety shoes when handling containers.
Storage	Store away from sources of strong heat and strong oxidising chemicals. Keep containers tightly closed in a cool dry, well ventilated place. Take precautionary measures to prevent spills into drains, soil or water. External tanks or stillage should be banded.

### 8. EXPOSURE CONTROLS & PERSONAL PROTECTION

#### Engineering Measures

Ensure good ventilation. Use protective equipment and/or local ventilation when needed. Avoid skin contact and inhalation of oil mist.

#### Exposure Values

Comply with current local occupation exposure limit.  
It is recommended that mineral oil mists are kept below  $5\text{mg}/\text{m}^3$  (8hr T.W.A. value) EH40.



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Morris & Company, Welsh Bridge, Shrewsbury

Registered in England No. 185693



Certificate No. EMS 60044  
BS EN ISO14001 1996

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Morris Hydraulic &  
Compressor Oils  
Page 3 of 5  
Number 200  
Revision: 4  
01.09.03

## Safety data sheet

### Protection and Hygiene

Wash hands before breaks and immediately after handling the product.  
Thoroughly clean contaminated skin and change dirty clothing and equipment.

### Respiratory Protection

Oil Mist : respirator (combined particle and organic vapour filter type A2/P2)

### Hand Protection

Protective gloves (PVC, Nitrile rubber). For further information consult glove manufacturer for recommendations of glove type associated with your particular application, so that breakthrough times can be assessed. Show this data sheet

### Eye Protection

Safety goggles if there is a risk of splashing

### Skin Protection

Protective clothing when needed.

## 9. PHYSICAL & CHEMICAL PROPERTIES: typical data

Appearance at 20°C	Mobile liquid
Odour	Oil
pH	Neutral
Density at 15°C	0.86 to 0.89g/cm <sup>3</sup>
Viscosity at 40°C	See appropriate I.S.O value
Flash Point (ASTM D93)	Greater than 150°C
Auto-ignition temperature (ASTM E659)	Greater than 300°C
Explosion Limits	N/A
Vapour pressure 20°C	<0.1 K Pa
Solubility	Insoluble in water. <0.1 g/l Soluble in mineral oils and non-polar solvents.

## 10. STABILITY & REACTIVITY

Hazardous Reactions Products of this type are stable and unlikely to react in a hazardous manner under normal conditions of use.

Thermal Decomposition This material is combustible.

Hazardous decomposition products, which can be formed on heating: Carbon monoxide, carbon dioxide, oxides of nitrogen and sulphur.

## 11. TOXICOLOGICAL INFORMATION

Eyes Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Skin Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Morris & Company, Welsh Bridge, Shrewsbury

Registered in England No. 185693



Certificate No. EMS 60044  
BS EN ISO14001 1996

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Morris Hydraulic &  
Compressor Oils  
Page 4 of 5  
Number 200  
Revision: 4  
01.09.03

## Safety data sheet

Inhalation	At normal ambient temperatures is unlikely to cause inhalation hazard because of low volatility.
Ingestion	Unlikely to cause harm if swallowed in small doses. Larger doses may cause nausea and diarrhoea.
Acute Toxicity	The refined mineral base oils used in this formulation are of low order of toxicity. LD50 (RAT) for base oil greater than 5g/kg.

### 12. ECOLOGICAL INFORMATION

Mobility	Product does not evaporate from surface soil or water. Some components may penetrate the soil causing ground water contamination.
Degradability	Inherently but not readily biodegradable.
Bio accumulation	No evidence to suggest bio-accumulation will occur.
Aquatic toxicity	Spills on water will form a film which may cause damage to organisms.

### 13. DISPOSAL CONSIDERATION

Waste	Send to a Registered Waste Disposal Site using the services of a Registered Waste Disposal Contractor. Ensure conformance with local and national regulations.
Packaging	Labels should not be removed from containers until they have been cleaned. Empty containers may contain hazardous residues. Ensure conformance with local and national regulations.
Specific Advice	As supplied material should be considered as Special Waste and Disposal should conform with the relevant Regulations.
General	Under no circumstances should this product be disposed of by putting into drains soil or water courses.

### 14. TRANSPORT INFORMATION

Not classified as Hazardous for Transport.

U.N. Number:	N/A	Packaging Group:	N/A
Shipping Name:	N/A		
IMO Class:	N/A	Marine Pollutant:	No
ADR/RID:	N/A	ICAO/IATA:	N/A



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Morris & Company, Welsh Bridge, Shrewsbury

Registered in England No. 185693



Certificate No. EMS 60044  
BS EN ISO14001 1996

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Morris Hydraulic &  
Compressor Oils  
Page 5 of 5  
Number 200  
Revision: 4  
01.09.03

## Safety data sheet

### 15. REGULATORY INFORMATION

Classification: This product is NOT classified for supply in the UK.

Statutory Instruments                      The Health & Safety at Work Act 1974.  
Consumer Protection Act.  
Environmental Protection Act.  
Guidance:                                        COSHH Regulations CHIP Regulations.  
CHIP for everyone COSHH Essentials

### 16. OTHER INFORMATION

Concawe Report No: 5/87 'Health aspects of lubricants.'

Risk. R Phases used in Section 2.

R51/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Original Issued date:                      03.03.94  
Revision: 4                                      Date: 01.09.03                                      Changes: Sections 11, 16

This information is, to the best of Morris & Company's knowledge, correct and is intended to describe the product requirements. Since the conditions of use are outside Morris & Company's control any recommendations or suggestions are made without guarantee and Morris & Company disclaims any liability for loss or damage suffered from use of this information. Customers must satisfy themselves that the product is suitable for a particular purpose. Furthermore, nothing contained herein shall be constructed as a recommendation to use any product in conflict with existing patents.



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Morris & Company, Welsh Bridge, Shrewsbury

Registered in England No. 185693



Certificate No. EMS 60044  
BS EN ISO14001 1996