

Type	Hose Size (bore)	Part number	Wire	Length		Max Working pressure (psi)	Breaking load (kg/mm2)	Material
Hose – Hose Standard	1/2” - 1 1/4”	WH3	3mm	20 1/2”	520mm	200	650	Wire Galvanised Steel, Spring Galvanised Steel, Ferrule Aluminium
	1/2” - 2”	WH5	5mm	28”	710mm	200	1750	
	1 1/2” - 3”	WH6	6mm	38 b1/4”	970mm	200	2100	
	4” - 6”	WH6-1	6mm	44”	1120mm	200	2100	
	4” - 6”	WH10	10mm	44”	1120mm	200	5600	
Hose – Hose short	3/16” - 1/2”	WH3-1	3mm	9 3/4”	250mm	200	650	
	3/16” - 1/2”	WH3-2	3mm	12 1/2”	320mm	200	650	
Hose – Hose Anti-Spark	1/2” - 1 1/4”	WH3C	3mm	20 1/2”	520mm	200	650	Wire Galvanised Steel, Spring Galvanised Steel, Ferrule Copper
	1/2” - 2”	WH5C	5mm	28”	710mm	200	1750	
	1 1/2” - 3”	WH6C	6mm	38 1/4”	970mm	200	2100	
	4” - 6”	WH6-1C	6mm	44”	1120mm	200	2100	
	4” - 6”	WH10C	10mm	44”	1120mm	200	5600	
Hose – Hose Stainless steel	1/2” - 1 1/4”	WH3S	3mm	20 1/2”	520mm	200	650	Wire Stainless steel 304, Spring Stainless steel 304, Ferrule Stainless steel 316
	1/2” - 2”	WH5S	5mm	28”	710mm	200	1750	
	1 1/2” - 3”	WH6S	6mm	38 1/4”	970mm	200	2100	
	4” - 6”	WH6-1S	6mm	44”	1120mm	200	2100	
	4” - 6”	WH10S	10mm	44”	1120mm	200	5600	